

Certificate of Constancy of Performance

This is to certify that:

The Parkside Group Ltd
Units 5
The Willow Centre
17 Willow Lane
Mitcham
Surrey
CR4 4NX
United Kingdom

Holds Certificate Number:

2797 CPR 752545

In respect of:

**EN 179:2008 – AXIM PR-7085-P Concealed Vertical Rods and PR-7095-P Rim Latch Push Pad Series
Emergency Exit Devices.
Mechanically operated by either a lever handle or a push pad for the purpose of achieving a safe exit
under an emergency situation on escape routes.**

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product(s). This certificate was first issued on the date below and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For and on behalf of BSI, a Notified
Body for the above Regulation
(Notified Body Number 2797):

Drs. Dave Hagenaaars, Managing Director

First Issued: 2022-11-29

Latest Issue: 2022-11-29

Page: 1 of 4



Certificate of Constancy of Performance

No. 2797 CPR 752545

EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 1: Requirements for emergency exit devices in line with EN 179:2008 (to be read in conjunction with Tables 2)		
Product:	Emergency exit devices operated by a lever handle or a push pad as covered by the scope of EN 179:2008.	
Intended use:	For single and double doors on escape routes.	
Essential characteristics	Clauses within EN 179:2008	Compliance
		PR-7085-P and PR-7095-P
Ability to release (for doors on escape routes)	4.2.1	Achieved
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Achieved where applicable
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	NPD <i>Note 2 applies</i>
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	NPD
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1	Not suitable for use on fire/smoke door assemblies– Grade 0
Control of Dangerous substances	4.1.29	Achieved
Note 1:	This details only those essential characteristics as required in the ZA Annex of EN 179:2008 and applicable to lever handle or a push pad operation.	
Note 2:	Re-engagement force may be omitted if the emergency exit device does not include an automatic re-latching device.	

First Issued: 2022-11-29

Latest Issue: 2022-11-29

Page: 2 of 4

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Certificate of Constancy of Performance

No. 2797 CPR 752545

EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 2: Product Information – Emergency Exit Devices not approved for use on fire / smoke door assemblies.			
No	Description	Additional Information	Model
1	Emergency exit device	Concealed rod Paddle PR-7085-Push Pad with LH725-AL lever OAD	PR-7085-P
2	Emergency exit device	Rim Mounted Paddle Exit Device Push Pad with LH750-AL Lever OAD	PR-7095-P
Note 1		Emergency exit devices detailed in table 2 have conformed to the requirements of EN 179:2008, Table 1: Performance characteristics and compliance criteria.	

First Issued: 2022-11-29

Latest Issue: 2022-11-29

Page: 3 of 4

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Certificate of Constancy of Performance

No. 2797 CPR 752545

EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Manufacturing Plant

Certified Activities

K/001

EN 179:2008 – Building hardware – Emergency exit devices operated by a lever handle or push pad, for use on escape routes.



First Issued: 2022-11-29

Latest Issue: 2022-11-29

Page: 4 of 4

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.