

UKCA Certificate of Constancy of Performance

This is to certify that:

The Parkside Group Ltd
Units 5
The Willow Centre
17 Willow Lane
Mitcham
Surrey
CR4 4NX
United Kingdom

Holds Certificate Number:

0086 CPR 752512

In respect of:

BS EN 179:2008 – AXIM PR-7085-P Concealed Vertical Rods and PR-7095-P Rim Latch Push Pad Series Emergency Exit Devices.
Mechanically operated by either a lever handle or a push pad for the purpose of achieving a safe exit under an emergency situation on escape routes.

In compliance with the Regulation (UK) Statutory Instrument 2019 No 465 of the United Kingdom Parliament (Construction Products (Amendment etc.) (EU Exit) Regulations or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product. This certificate was first issued on the date below and will remain valid as long as neither the designated standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the approved product certification body.

For and on behalf of BSI, an Approved Body for the above Regulation (Approved Body Number 0086):

Shahm Barhom, Group Product Certification Director

First Issued: 2022-11-09

Effective Date: 2022-11-09

Latest Issue: 2022-11-09

Page: 1 of 4



UKCA Certificate of Constancy of Performance

No. 0086 CPR 752512

BS EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 1: Requirements for emergency exit devices in line with BS EN 179:2008 (to be read in conjunction with Tables 2)		
Product:	Emergency exit devices operated by a lever handle or a push pad as covered by the scope of BS EN 179:2008.	
Intended use:	For single and double doors on escape routes.	
Essential characteristics	Clauses within BS EN 179:2008	Compliance
		PR-7085-P and PR-7095-P
Ability to release (for doors on escape routes)	4.2.1	Achieved
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Achieved where applicable
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	NPD <i>Note 2 applies</i>
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	NPD
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1	Not suitable for use on fire/smoke door assemblies– Grade 0
Control of Dangerous substances	4.1.29	Achieved
Note 1:	This details only those essential characteristics as required in the ZA Annex of BS EN 179:2008 and applicable to lever handle or a push pad operation.	
Note 2:	Re-engagement force may be omitted if the emergency exit device does not include an automatic re-latching device.	

First Issued: 2022-11-09

Effective Date: 2022-11-09

Latest Issue: 2022-11-09

Page: 2 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 752512

BS EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 2: Product Information – Emergency Exit Devices not approved for use on fire / smoke door assemblies.

No	Description	Additional Information	Model
1	Emergency exit device	Concealed rod Paddle PR-7085-Push Pad with LH725-AL lever OAD	PR-7085-P
2	Emergency exit device	Rim Mounted Paddle Exit Device Push Pad with LH750-AL Lever OAD	PR-7095-P
Note 1:		Emergency exit devices detailed in table 2 have conformed to the requirements of BS EN 179:2008, Table 1: Performance characteristics and compliance criteria.	

First Issued: 2022-11-09

Effective Date: 2022-11-09

Latest Issue: 2022-11-09

Page: 3 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 752512

BS EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Manufacturing Plant

Certified Activities

K/001

BS EN 179:2008 – Building hardware – Emergency exit devices operated by a lever handle or push pad, for use on escape routes.



First Issued: 2022-11-09

Effective Date: 2022-11-09

Latest Issue: 2022-11-09

Page: 4 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.